

WAAS CH 86830 W02B	APP CRS 015°	Rwy Idg 7571 TDZE 754 Apt Elev 759
--	------------------------	---

RNAV (GPS) RWY 2L
DUPAGE (DPA)

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Aurora altimeter setting; increase LPV DA to 991 feet, LNAV/VNAV DA to 1151 feet and visibility LNAV/VNAV all Cats ½ SM; increase all MDA 40 feet and visibility LNAV Cat C/D ½ SM and Circling Cat C/D ¼ SM. For inop MALSR, increase LNAV/VNAV all Cats visibility to 1½ mile and LNAV Cat C/D visibility to 1½ mile. For inop MALSR when using Aurora altimeter setting, increase LNAV/VNAV all Cats visibility to 1½ and LNAV Cat C/D visibility to 1½ mile. VDP and Baro-VNAV NA when using Aurora altimeter setting. Circling Rwy 15, 28, 33 NA at night.

MALSR

MISSED APPROACH:
Climb to 1300 then
climbing left turn to
3000 direct NUELG
and hold.

ATIS 132.075	CHICAGO APP CON 133.5 349.0	DUPAGE TOWER 120.9 257.8	GND CON 121.8	CLNC DEL 119.75
-----------------	--------------------------------	-----------------------------	------------------	--------------------

