

WAAS
CH **57910**
W25A

APP CRS
252°

Rwy Idg
TDZE
Apt Elev

6499
647
648

RNAV (GPS) RWY 25

WHITESIDE COUNTY/JOS H BITTORF FLD (SQI)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Circling Rwy 36 NA at night.
DME/DME RNP-0.3 NA.

MALSR

MISSED APPROACH: Climb to 2700 direct KEBEY and hold.

AWOS-3PT
119.175

ROCKFORD APP CON
126.0 327.0

CLNC DEL
128.0

UNICOM
123.0 (CTAF) 0

MSA RW25 25 NM
2500

Procedure NA for arrival on PLL VOR/DME airway radials 085 CW 180.

POLO PLL
2500 132° (2.7)
(IAF) VOSUY

2500 NoPT
6°

4 NM
072°
252°

(IF/IAF) HELEG

2500 NoPT
3.67° (6)

(IAF) TEVUE

2500 334° (14.9)

TRIDE

Procedure NA for arrivals at TRIDE on V8-38 northeast bound.

MISSED APCH FIX
KEBEY
072°
252°
4 NM

1001
1120
823
779±
807
RW25

COVKA 2.1 NM to RW25
(FAF) FOVON

1499

ELEV 648

TDZE 647

81
3900 X 100
701
36
6499 X 150
252° to RW25

HIRL Rwy 7-25 0

MIRL Rwy 18-36 0

REIL Rwy 7, 18 and 36 0

2700

↑

KEBEY

* LNAV only.

COVKA 2.1 NM to RW25

FOVON 2500

HELEG

4 NM Holding Pattern

* 1.1 NM to RW25

* 1360

2500

2500

GP 3.00° TCH 54

1.1 NM

1 NM

3.6 NM

6 NM

CATEGORY	A	B	C	D
LPV DA	847-1/2	200 (200-1/2)		
LNAV/VNAV DA	1047-7/8	400 (400-7/8)		
LNAV MDA	1040-1/2 393 (400-1/2)	1040-5/8 393 (400-5/8)		
CIRCLING	1140-1 492 (500-1)	1160-1 512 (600-1/2)	1480-2 832 (900-2 3/4)	

STERLING ROCKFALLS, ILLINOIS
Amdt 1 19JUL18

41°45'N-89°41'W

WHITESIDE COUNTY/JOS H BITTORF FLD (SQI)
RNAV (GPS) RWY 25