




WAAS CH 58112 W05A	APP CRS 050°	Rwy Idg TDZE 123 Apt Elev 125
--	------------------------	---

RNAV (GPS) RWY 5
BARTOW EXEC (BOW)

RNP APCH. ▼ Rwy 5 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Tampa Intl altimeter setting and increase LPV DA to 553 feet, LNAV/VNAV DA to 684 feet and all MDA 120 feet, increase LNAV Cat C visibility ¼ SM, Cat D ½ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. VDP and Baro-VNAV NA when using Tampa Intl altimeter setting. ▲	MISSED APPROACH: Climb to 2300 direct ZOMOV and hold.
--	--

AWOS-3 123.775	TAMPA APP CON 120.65 290.3	BARTOW TOWER ★ 121.20 (CTAF)	GND CON 121.9	UNICOM 122.95
--------------------------	--------------------------------------	--	-------------------------	-------------------------



CATEGORY	A	B	C	D
LPV DA	447-1¼	324 (400-1¼)		
LNAV/VNAV DA	509-1½	386 (400-1½)		
LNAV MDA	520-1 397 (400-1)	520-1 397 (400-1½)	520-1 397 (400-1½)	520-1 397 (400-1½)

SE-3, 19 MAY 2022 to 16 JUN 2022

SE-3, 19 MAY 2022 to 16 JUN 2022