

WAAS CH 53410 W10A	APP CRS 104°	Rwy Idg TDZE 6591 Apt Elev 6606
--	------------------------	---

RNAV (GPS) Y RWY 10

YAMPA VALLEY (HDN)

RNP APCH-GPS.

▼

Rwy 10 helicopter visibility reduction below ¾ SM NA.

⚠

Inop table does not apply to *LPV all Cats, LNAV/VNAV all Cats, and LNAV Cats C/D. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -28°C or above 54°C.

MALSF

MISSED APPROACH: Climb to 13700 direct OBTUE and on track 124° to TILLI and hold, continue climb-in-hold to 13700.
* Missed approach requires minimum climb of 295 feet per NM to 8700.

AWOS-3 119.275	DENVER CENTER 120.475 235.975	UNICOM 123.0 (CTAF)
--------------------------	---	-------------------------------

ELEV 6606	D	TDZE 6591
-----------	----------	-----------

104° to RW10

6639

0.3% DOWN

10000 X 150

7 NM Holding Pattern

REVME

14000 ← 284°

10000 → 104°

GP 3.00°

TCH 55

INEDE

8700

104°

8700

6.8 NM

3 NM

3.5 NM

RW10

13700

OBTUE

tr 124°

TILLI

CATEGORY	A	B	C	D
LPV DA*	6791-¾ 200 (200-¾)			
LPV DA	7327-1¾ 736 (800-1¾)			
LNAV/VNAV DA	7966-5 1375 (1400-5)			
LNAV MDA	7760-1 1169 (1200-1)	7760-1¼ 1169 (1200-1¼)	7760-3	1169 (1200-3)
CIRCLING	7760-1¼ 1154 (1200-1¼)	7760-1½ 1154 (1200-1½)	7760-3	8180-3 1574 (1600-3)

HAYDEN, COLORADO
Amdt 4 24MAR22

40°29'N-107°13'W

YAMPA VALLEY (HDN)

RNAV (GPS) Y RWY 10