


WAAS CH 45933 W31A	APP CRS 315°	Rwy Idg TDZE 820 Apt Elev 820
--	------------------------	---

RNAV (GPS) RWY 31

HALLOCK MUNI (HCO)

RNP APCH-GPS.	MISSED APPROACH: Climb to 3300 direct FESNI and hold, continue climb-in-hold to 3300.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Grafton altimeter setting and increase LPV DA To 1082 feet; increase LNAV/VNAV DA to 1132 feet; increase all MDAs 80 feet and LNAV visibility Cat C ¾ SM, and Circling visibility Cat C ¼ SM. Baro-VNAV and VDP NA when using Grafton altimeter setting.	

AWOS-3 126.475	MINNEAPOLIS CENTER 132.15 269.6	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



REIL Rwy 13 and 31 **L**
 MIRL Rwy 13-31 **L**

CATEGORY	A	B	C	D
LPV DA	1020-1	200 (200-1)		NA
LNAV/VNAV DA	1070-1	250 (300-1)		NA
LNAV MDA	1200-1	380 (400-1)		NA
C CIRCLING	1380-1	560 (600-1)	1380-1½ 560 (600-1½)	NA