


LOC/DME I-SAT 109.7 Chan 34	APP CRS 037°	Rwy ldg 8505 TDZE 786 Apt Elev 809
---	------------------------	---


ILS or LOC RWY 4
SAN ANTONIO INTL (SAT)

▼ Inop table does not apply to S-ILS 4. Circling NA west of Rwy 4 and 13R. Autopilot coupled approach NA below 1189. For inop ALS, increase S-LOC 4 Cat D visibility to 1¼ SM. ZINON fix minimums: for inop ALS, increase S-LOC 4 Cat D visibility to RVR 5000.	MALS 	MISSED APPROACH: Climb to 1700 then climbing left turn to 3500 on heading 025° and SAT VORTAC R-040 to SHEPE INT/SAT 18.4 DME and hold.
--	----------	---

D-ATIS 118.9	SAN ANTONIO APP CON 125.1 307.0	SAN ANTONIO TOWER 119.8 257.8	GND CON 121.9 348.6	CLNC DEL 126.7	CPDLC
------------------------	---	---	-------------------------------	--------------------------	-------



VGS and ILS glidepath not coincident (VGS Angle 3.00/TCH 79).				
TRAGO INT I-SAT 21.6	HARDD INT I-SAT 14.8	RESOC INT I-SAT 9.9	NADBE INT I-SAT 6.8	ZINON I-SAT 3.3
4000	3500	3500	2500	1220
GS 3.00° TCH 56	6.8 NM	4.9 NM	3.2 NM	3.5 NM
CATEGORY	A	B	C	D
S-ILS 4	986/40		200 (200-¾)	
S-LOC 4	1220/40	434 (500-¾)	1220/50	434 (500-1)
CIRCLING	1300-1 491 (500-1)	1400-1 591 (600-1)	1420-1¾ 611 (700-1¾)	1520-2¼ 711 (800-2¼)
ZINON FIX MINIMUMS (DME REQUIRED)				
S-LOC 4	1120/40	334 (400-¾)		
CIRCLING	1300-1 491 (500-1)	1400-1 591 (600-1)	1420-1¾ 611 (700-1¾)	1520-2¼ 711 (800-2¼)



SC-3, 16 JUN 2022 to 14 JUL 2022

SC-3, 16 JUN 2022 to 14 JUL 2022