

WAAS
CH **90503**
W19A

APP CRS
190°

Rwy Idg
TDZE **20**
Apt Elev **20**

6001

20

20

RNAV (GPS) RWY 19

NORTHEASTERN RGNL (EDE)

RNP APCH.

Baro-VNAV NA when using Elizabeth City altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 43°C. When local altimeter setting not received, use Elizabeth City altimeter setting and increase LPV DA to 275 LNAV/VNAV DA to 325 and all MDA 60 feet, increase LPV all Cats and LNAV Cat C/D visibility ¼ mile and LNAV/VNAV visibility all Cats ¼ mile. VDP NA when using Elizabeth City altimeter setting.

MISSED APPROACH:
Climb to 600 then right turn to 2500 direct IDWAP and hold.

AWOS-3 118.275	WASHINGTON CENTER 123.85 279.65	UNICOM 123.0 (CTAF) 0
--------------------------	---	---------------------------------

VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 48).		600	2500	IDWAP
4 NM Holding Pattern		↑	↷	✧
2500 ← 010° 190° →		*LNAV only.		
GP 3.00° TCH 43		*0.9 NM to RWY 19		
IDWAP		RWY 19		
EYUFI		ZAKUN 1.6 NM to RWY 19		
1600		*560		
6 NM		3.2 NM		
0.7		0.9		
CATEGORY	A	B	C	D
LPV DA		220- ³ / ₄	200 (200- ³ / ₄)	
LNAV/VNAV DA		270- ³ / ₄	250 (300- ³ / ₄)	
LNAV MDA		340-1	320 (400-1)	
CIRCLING	520-1	500 (500-1)	560-1 ¹ / ₂ 540 (600-1 ¹ / ₂)	580-2 560 (600-2)

EDENTON, NORTH CAROLINA
Amdt 2C 20MAY21

36°02'N-76°34'W

NORTHEASTERN RGNL (EDE)
RNAV (GPS) RWY 19