

WAAS CH 50212 W27A	APP CRS 270°	Rwy Idg TDZE 1230 Apt Elev 1230
--	------------------------	---

RNAV (GPS) RWY 27

GOGEBIC/IRON COUNTY (IWD)


RNP APCH - GPS.

Inoperative table does not apply to LPV and LNAV/VNAV all Cats and LNAV Cats A and B. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C. When using Ashland altimeter setting: inop table does not apply to LNAV/VNAV all Cats and LNAV Cat A. When using Ashland altimeter setting: for inoperative MALS, increase LNAV Cat B visibility to 1¼ mile. Baro-VNAV and VDP NA when using Ashland altimeter setting. When local altimeter setting not received, use Ashland altimeter setting: increase LPV DA to 1562 feet; increase LNAV/VNAV DA to 2298 feet and Cat C visibility ¼ SM; increase all MDA 140 feet and LNAV Cat C/D visibility ½ SM and Circling Cat B visibility ¼ SM.


MALS

MISSED APPROACH:
Climb to 3500 direct
GODSE and hold.

AWOS-3PT 125.175	MINNEAPOLIS CENTER 133.55	UNICOM 122.8 (CTAF) 0
----------------------------	-------------------------------------	---------------------------------



ELEV 1230	D	TDZE 1230
-----------	----------	-----------



3500	GODSE	* LNAV only	HIRUN	4 NM Holding Pattern
		BADVE 2.6 NM to RW27	PETFI	
		* 1.9 NM to RW27	CRAAG	
		RW27		
		2100*	3000	
		1.9	0.7	2.7 NM
				3.6 NM
				2.4 NM
CATEGORY	A	B	C	D
LPV DA	1430-1		200 (200-1)	
LNAV/ VNAV DA	2166-2	936 (1000-2)	2166-2¾ 936 (1000-2¾)	2166-3 936 (1000-3)
LNAV MDA	1900-1	670 (700-1)	1900-1¼ 670 (700-1¼)	1900-1½ 670 (700-1½)
CIRCLING	2100-1¼	870 (900-1¼)	2200-3 970 (1000-3)	2220-3 990 (1000-3)