

WAAS CH 73025 W27A	APP CRS 272°	Rwy Idg TDZE 925 Apt Elev 925
--	------------------------	---

RNAV (GPS) RWY 27

PORTLAND MUNI (PLD)


▼

▲ NA

DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Fort Wayne Intl altimeter setting and increase all MDAs 100 feet and visibility Cat C ½ SM. When VGSI inop, Straight-in/Circling Rwy 27 procedure NA at night. When VGSI inop, Circling Rwy 9 NA at night.

MISSED APPROACH:
Climb to 2500 direct
DIYEC and hold.

AWOS-3 124.675	FORT WAYNE APP CON 132.15 (SE/NE) 284.6 127.2 (SW/NW) 284.6	UNICOM 122.8 (CTAF) 0
--------------------------	---	--



ELEV 925	TDZE 925
-----------------	-----------------

2500

DIYEC

0.3% UP

4002 X 75

272° to RW 27

VGSI and descent angles not coincident
(VGSI Angle 3.00/TCH 26).

4 NM Holding Pattern

MAPOL

092° → 3000

← 272°

WEPRI 2.4 NM to RW27

DANCER

272°

3.00° TCH 40

2500

1720

2.4 NM

2.4 NM

6.1 NM

CATEGORY	A	B	C	D
LP MDA	1300-1 375 (400-1)			NA
LNAV MDA	1380-1	455 (500-1)	1380-1 455 (500-1 3/4)	NA
CIRCLING	1480-1	555 (600-1)	1580-1 655 (700-1 3/4)	NA