

LOC I-RYY	APP CRS	Rwy ldg	5374
111.9	273°	TDZE	1011
		Apt Elev	1040

ILS or LOC RWY 27


COBB COUNTY INTL/MCCOLLUM FLD (RYY)

RADAR required for procedure entry.


MAJLS MISSED APPROACH: Climb to 1600 then climbing right turn to 4000 on heading 050° and ATL VORTAC R-351 to FENTS INT/RMG 26.2 DME and hold, continue climb-in-hold to 4000.

⚠ Circling to Rwy 9 NA at night. When local altimeter setting not received, use Hartsfield-Jackson Atlanta Intl altimeter setting and increase all DA/MDA 60 feet; increase S-ILS 27 all Cats and CUMAV Fix Minimums S-LOC 27 Cats C and D visibility 1/2 mile; increase S-LOC 27 Cat B, Circling Cat A and B, and CUMAV Fix Minimums Circling Cat A and B visibility 1/4 mile; increase S-LOC 27 Cats C and D visibility 1/2 mile.

ATIS 128.125	ATLANTA APP CON 121.0 268.7	MCCOLLUM TOWER ★ 125.9 (CTAF) 0	GND CON 119.0	CLNC DEL 119.0 268.7	UNICOM 122.7
------------------------	---------------------------------------	---	-------------------------	--------------------------------	------------------------



ELEV 1040	D TDZE 1011
-----------	--------------------



CATEGORY	A	B	C	D
S-ILS 27	1211-3/4 200 (200-3/4)			
S-LOC 27	1700-1	689 (700-1)	1700-2	689 (700-2)
CIRCLING	1800-1	760 (800-1)	2220-3	1180 (1200-3)
CUMAV FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)				
S-LOC 27	1460-1	449 (500-1)	1460-1 3/8	449 (500-1 3/8)
CIRCLING	1800-1	760 (800-1)	2220-3	1180 (1200-3)

HIRL Rwy 9-27 **0**
FAF to MAP 6.1 NM

Knots	60	90	120	150	180
Min:Sec	6:06	4:04	3:03	2:26	2:02

SE-4, 16 JUN 2022 to 14 JUL 2022

SE-4, 16 JUN 2022 to 14 JUL 2022