

WAAS
CH **50139**
W34A

APP CRS
337°

Rwy Idg
TDZE **769**
Apt Elev **774**

5001
769
774

RNAV (GPS) RWY 34
CASTROVILLE MUNI (CVB)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Lackland AFB (Kelly Fld Annex) altimeter setting: increase all DA/MDA 60 feet and all visibilities ¼ mile. Helicopter visibility reduction below ¾ SM NA. Night landing: Rwy 16 NA.

MISSED APPROACH: Climb to 1300 then climbing left turn to 3000 direct SHEOL and hold.

AWOS-3 119.25	HDO ASOS 119.675	SAN ANTONIO APP CON 118.05 353.5	UNICOM 122.8 (CTAF) 0
-------------------------	----------------------------	--	---------------------------------

ELEV **774**

TDZE **769**

1300 3000 SHEOL				4 NM Holding Pattern			
*LNAV only. TAAHD 1.6 NM to RW34 IBDOW 2500 RW34 *1300 2500 337° 157° 3000 GP 3.00° TCH 40							
1.6 NM				3.7 NM			
6 NM							
CATEGORY	A	B	C	D			
LPV DA	1019-7/8 250 (300-7/8)			NA			
LNAV/VNAV DA	1127-1¼ 358 (400-1¼)			NA			
LNAV MDA	1200-1	431 (500-1)	1200-1½ 431 (500-1½)	NA			
CIRCLING	1200-1 426 (500-1)	1380-1 606 (700-1)	1580-2¼ 806 (900-2¼)	NA			

CASTROVILLE, TEXAS

Amtd 1 15OCT15

29°21'N-98°51'W

CASTROVILLE MUNI (CVB)
RNAV (GPS) RWY 34