WAAS	APP CRS	Rwy Idg	5006
CH 70519	332°	TDZE	131
W33A		Apt Elev	132

RNAV (GPS) RWY 33

CURTIS L BROWN JR FIELD (EYF)

RNP APCH.

Rwy 33 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Fayetteville, NC altimeter setting; increase LPV DA to 453 feet, LNAV/VNAV DA to 537 feet, and all MDAs 80 feet, and increase LPV and LNAV/VNAV all Cats visibility ¼ SM, LNAV Cats C and D and Circling Cats C and D visibility ¼ SM. Baro-VNAV and VDP NA when using Fayetteville, NC altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F).

MISSED APPROACH: Climb to 3100 direct EXBEL and hold.

AWOS-3P	FAYETTEVILLE APP CON	UNICOM
119.475	133.0 290.25	122.8 (CTAF) L



ELEV 132 TDZE 131



REIL Rwys 15 and 33 L
MIRL Rwy 15-33 L



CATEGORY	A	B	C	D
LPV DA	381-¾		250 (300-¾)	
LNAV/VNAV DA	465-1¼		334 (400-1¼)	
LNAV MDA	580-1	449 (500-1)	580-1¼ 449 (500-1¼)	580-1½ 449 (500-1½)
CIRCLING	580-1 448 (500-1)	660-1 528 (600-1)	880-2¼ 748 (800-2¼)	880-2½ 748 (800-2½)

SE-2, 16 JUN 2022 to 14 JUL 2022
SE-2, 16 JUN 2022 to 14 JUL 2022