
TOP ALTITUDE: ASSIGNED BY ATC
TAKEOFF MINIMUMS
Rwy 8R: FLOGS and NOCHI transitions standard with minimum climb of 500' per NM to 6000. GREBE and SLNNK transitions standard with minimum climb of 500' per NM to 13500.
Rwy 22: FLOGS and NOCHI transitions standard with minimum climb of 515' per NM to 7200. GREBE and SLNNK transitions standard with minimum climb of 515' per NM to 13500.
Rwy 26L: FLOGS and NOCHI transitions standard with minimum climb of 570' per NM to 6800. GREBE and SLNNK TRANSITIONS standard with minimum climb of 570' per NM to 13500.
R-5107A
NOTE: Takeoff Rwy 8R, do not exceed 220K until passing JAPOD.
NOTE: Takeoff Rwy 26L, do not exceed 220K until passing 4462.
NOTE: For use by Turbojet aircraft only.
NOTE: RADAR required for non-GPS equipped aircraft.
NOTE: DME/DME/IRU or GPS required.
NOTE: RNAV 1.
NOTE: Chart not to scale.
D-ATIS 120.0 254.3
CLNC DEL 125.0 379.1
GND CON 121.9 348.6
EL PASO TOWER 118.3 239.275
EL PASO DEP CON 119.15 263.0
ALBUQUERQUE CENTER 128.2 285.5
SLNNK
BOATY
RUTER
GREBE
FEPOX 15000
JEBSU 13000
ATKNN
ZILEK
HAVID
ALIBY
FLOGS
NOCHI
BIVKE
JAPOD 220K
R-5115
N
FL180 *9800 004° (23)
FL180 *9800 318° (60)
FL180 *12400 304° (85)
309° 17600 * 0690 (13)
15000 *6800 307° (7)
13000 *9400 343° (14)
10500 *7400 (12) 274°
10500 *6800 (12) 270°
FL180 *8200 268° (49)
FL180 *17000 274° (122)
FL180 *16100 266° (101)
4462
265° 22°
085°
6000
(5) 296°
282° (10)
(NARRATIVE ON FOLLOWING PAGE)