
## RDHWK THREE DEPARTURE (RNAV)



TOP ALTITUDE: ASSIGNED BY ATC D-ATIS 125.85 CLNC DEL 124.35 GND CON 121.9 348.6 ROGERS TOWER 119.35 269.45 OKE CITY DEP CON 124.2 336.4

NOTE: RADAR required.


NOTE: DME/DME/IRU or GPS required.

NOTE: RNAV 1.

## TAKEOFF MINIMUMS:

Rwy 13, 17L/R, 18, 31, 35L/R, 36:

Standard with minimum climb of  $500^{\circ}$  per NM to 1800.



NOTE: Chart not to scale.

to 08 SEP 2022

SC-1, 11 AUG 2022

## V

## DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 13: Climb heading 131° to 1800, then right turn heading 176° or as assigned by ATC, expect RADAR vectors to OHYOU, thence. . . .

TAKEOFF RWY 17L/R, 18: Climb heading 176° to 1800, then heading 176° or as assigned by ATC, expect RADAR vectors to OHYOU, thence. . . .

TAKEOFF RWY 31: Climb heading 311° to 1800, then right turn heading 011° or as assigned by ATC, expect RADAR vectors to OHYOU, thence. . . .

TAKEOFF RWY 35L/R, 36: Climb heading 356° to 1800, then right turn heading 011° or as assigned by ATC, expect RADAR vectors to OHYOU, thence. . . .

....on track 100° to RDHWK, then on (transition). Maintain 5000 or as assigned by ATC. Expect filed altitude 10 minutes after departure.

HOLLE TRANSITION (RDHWK3.HOLLE):