

LOC I-FOD 109.1	APP CRS 063°	Rwy Idg 6547 TDZE 1107 Apt Elev 1156
---------------------------	------------------------	---

ILS or LOC RWY 6

FORT DODGE RGNL (FOD)

ADF required. RADAR required for procedure entry at SHRLA.

NA

DME from FOD DME. Simultaneous reception of I-FOD and FOD DME required. For inop ALS, increase S-LOC 6 Cat C/D visibility to 1½ SM.

MALSR

MISSED APPROACH: Climb to 2800 then left turn direct BARRO LOM and hold.

AWOS-3PT 118.775	MINNEAPOLIS CENTER 134.0 288.3	UNICOM 123.0 (CTAF)
----------------------------	--	-------------------------------

Procedure NA for arrival on MCW VOR/DME radials 230 CW 278.

CRYPT CENTRAL MOA

CRYPT SOUTH MOA

2800 NoPT 063° (10)

(IF) SHRLA FOD 13.9 RADAR

243°

018°

063°

243°

LOM/IAF BARRO 341 FO

LOCALIZER 109.1 I-FOD

MASON CITY 114.9 MCW Chan 96

2800 to LOM 225° (55.4)

MSA FO 25 NM

3400

090°

2800

ELEV 1156	TDZE 1107
-----------	-----------

Remain within 10 NM

2800

243°

063°

2800

GS 3.00° TCH 54

4.9 NM

2800

FO

2680

243°

063°

2800

4.9 NM

CATEGORY	A	B	C	D
S-ILS 6	1307-½ 200 (200-½)			
S-LOC 6	1600-½	493 (500-½)	1600-1	493 (500-1)
CIRCLING	1600-1 444 (500-1)	1620-1 464 (500-1)	1740-1½ 584 (600-1½)	2080-3 924 (1000-3)

MIRL Rwy 12-30

REIL Rwys 12, 24 and 30

HIRL Rwy 6-24

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

FORT DODGE, IOWA

Amdt 8 14JUL22

42°33'N-94°12'W

FORT DODGE RGNL (FOD)

ILS or LOC RWY 6