



WAAS CH 86538 W29A	APP CRS 289°	Rwy Idg TDZE Apt Elev	5400 97 97
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 29

ANIAK (ANI)(PANI)

RNP APCH. ⚠ Circling NA north of Rwy 11-29. Rwy 29 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. ❄ -38°C		MISSED APPROACH: Climb to 1500 then climbing left turn to 3500 direct APWIS and hold.	
AWOS-3P 124.3	ANCHORAGE CENTER 118.15 251.05	CLNC DEL 118.15	CTAF 122.1



1500	3500	APWIS	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 40).			
*LNAV only		HAFRU	APWIS	4 NM Holding Pattern		
*1.3 NM to RW29		1700	289°	109°	14000	GP 3.00°
1.3 NM		3.6 NM	6.2 NM	289°	3500	TCH 52
CATEGORY	A	B	C	D		
LPV DA	347-1		250 (300-1)			
LNAV/VNAV DA	460-1		363 (400-1)			
LNAV MDA	560-1	463 (500-1)	560-1 3/8	463 (500-1 3/8)		
CIRCLING	560-1 463 (500-1)	620-1 523 (600-1)	860-2 1/4 763 (800-2 1/4)	1200-3 1103 (1200-3)		