

OAKLAND FIVE DEPARTURE

AL-294 (FAA)

METRO OAKLAND INTL (OAK)
OAKLAND, CALIFORNIA

D-ATIS
133.775
CLNC DEL
121.1
CPDLC
NORCAL DEP CON
120.9 323.2

TOP ALTITUDE:
ASSIGNED BY ATC

MENDOCINO
112.3 ENI
Chan 70
N39°03.19'-W123°16.46'
L-2, H-3

RED BLUFF
115.7 RBL
Chan 104
N40°05.93'-W122°14.18'
L-2, H-3

SACRAMENTO
115.2 SAC
Chan 99
N38°26.62'-W121°33.10'
L-2-3, H-3

SCAGGS ISLAND
112.1 SGD
Chan 58
N38°10.76'-W122°22.39'
L-2-3

GRTFL
DEDHD


ORRCA
MOGEE

TIPRE

SYRAH

LINDEN
114.8 LIN
Chan 95
N38°04.47'-W121°00.23'
L-2-3, H-3

ALCOA
N37°50.00'-W125°50.07'
H-3



BEBOP
N37°00.00'-W125°00.07'
H-3

SEGUL
N36°57.78'-W122°34.33'
△

WOODSIDE
113.9 OSI
Chan 86
N37°23.55'-W122°16.88'
L-2-3, H-3

NTELL

CINNY

CYPRS
N36°25.34'-W122°25.93'
△

PANOCHÉ
112.6 PXN
Chan 73
N36°42.93'-W120°46.72'
L-3, H-3

EBAYE
LOSHN

CISCO

AVENAL
117.1 AVE
Chan 118
N35°38.82'-W119°58.72'
L-3-7, H-4

FELLOWS
117.5 FLW
Chan 122
N35°05.59'-W119°51.93'
L-3-7, H-4

NOTE: Chart not to scale.

TAKEOFF MINIMUMS

Rwys 15, 33: NA- ATC.
Rwy 10L: Standard with minimum climb of 340' per NM to 2300.
Rwy 10R: Standard with minimum climb of 330' per NM to 2300.
Rwy 12: Standard with minimum climb of 270' per NM to 1400.
Rwys 28L/R, 30: Standard with minimum climb of 375' per NM to 2000.

NOTE: RADAR required.
NOTE: DME required.
NOTE: Use the SILENT, HUSSH, or SUNNE DEPARTURE during the periods of 2200-0700 local in lieu of the OAKLAND DEPARTURE.

(NARRATIVE ON FOLLOWING PAGE)

OAKLAND FIVE DEPARTURE

SW-2, 08 SEP 2022 to 06 OCT 2022

SW-2, 08 SEP 2022 to 06 OCT 2022