

WAAS CH 42700 W28A	APP CRS 281°	Rwy Idg TDZE Apt Elev	6003 85 85
--	------------------------	-----------------------------	---------------------------------------


RNAV (GPS) RWY 28
MILLVILLE MUNI (MIV)

RNP APCH-GPS.


T Circling Rwy 32 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Atlantic City altimeter setting and increase all DA/MDA 60 feet; increase LNAV/VNAV all Cats, LNAV Cats C/D and Circling Cat C visibility ¼ mile. VDP and Baro-VNAV NA when using Atlantic City altimeter setting.

MISSED APPROACH: Climb to 2000
direct TIYDU and right turn on track
030° to RUPDE and right turn 077°
track to VCN VOR/DME and hold.

ASOS 119.6	ATLANTIC CITY APP CON 124.6 327.125	UNICOM 123.0 (CTAF) 0
----------------------	---	---------------------------------




ELEV 85		TDZE 85
---------	--	---------



2000 TIYDU  tr 030° RUPDE  tr 077° VCN 

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/ TCH 29)

*LNAV only



CATEGORY	A	B	C	D
LPV DA		344-1	259 (300-1)	
LNAV/ VNAV		405-1	320 (400-1)	
LNAV MDA	640-1	555 (600-1)	640-1 ½ 555 (600-1 ½)	640-1 ¾ 555 (600-1 ¾)
CIRCLING	640-1	555 (600-1)	660-1 ½ 575 (600-1 ½)	660-2 575 (600-2)