

WAAS

CH **58304**

W36A

APP CRS

005°

Rwy Idg

5264

TDZE

759

Apt Elev

777

RNAV (GPS) RWY 36

AUBURN UNIVERSITY RGNL (AUO)

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Columbus altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Columbus altimeter setting: increase LPV DA to 1072 feet and visibility all Cats ½ SM; increase LNAV/VNAV DA to 1173 feet and visibility all Cats ¾ SM; increase all MDA 120 feet and LNAV Cats C/D visibility ¼ SM and Circling Cats C/D visibility ½ SM. For inop ALS, increase LNAV/VNAV Cat D visibility ¼ SM and LNAV Cat D visibility ½ SM. For inop ALS, when using Columbus altimeter setting, increase LPV all Cats visibility to 1 ½ SM, LNAV/VNAV all Cats visibility to 1 ½ SM, and LNAV all Cats visibility to 1 ¾ SM.

MALSF

MISSED APPROACH:

Climb to 3000 direct RIVME and hold.

AWOS-3PT 132.575	ATLANTA APP CON ★ 125.5 323.1	CLNC DEL 118.7	UNICOM 123.0 (CTAF) 0
----------------------------	---	--------------------------	---------------------------------

4 NM Holding Pattern		HESEL		AUBIE		PIROE		RW36							
3000		185°		005°		005°		005°							
GP 3.00°		TCH 44		2600		*1660		*1.1 NM to RW36							
7 NM		2.9 NM		1.7 NM		1.1 NM		0.9% UP							
CATEGORY	A	B	C	D											
LPV DA	959-¾				200 (200-¾)										
LNAV/VNAV DA	1060-⅞				301 (300-⅞)										
LNAV MDA	1120-¾	361 (400-¾)	1120-⅞	361 (400-⅞)											
CIRCLING	1280-1 503 (600-1)	1360-1 583 (600-1)	1380-1¾ 603 (700-1¾)	1480-2¼ 703 (800-2¼)											

ELEV 777

TDZE 759

3000

RIVME

4000 X 75

5264 X 100

0.9% UP

36

005° to RW36

MIRL Rwy 11-29

HIRL Rwy 18-36

AUBURN, ALABAMA

Amdt 2C 10NOV16

32°37'N-85°26'W

AUBURN UNIVERSITY RGNL (AUO)

RNAV (GPS) RWY 36