

WAAS

CH **90107**

W27A

APP CRS

273°

Rwy Idg

5004

TDZE

1184

Apt Elev

1184

RNAV (GPS) RWY 27

WASHINGTON COUNTY (AFJ)

RNP APCH-GPS.

▼

Circling NA for Cat D N of Rwy 9-27. Rwy 27 helicopter visibility reduction below ¾ SM NA.

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Circling Rwy 9 NA at night.

MISSED APPROACH: Climb to 1700 then climbing right turn to 3300 direct HLG VOR/DME and hold.

AWOS-3PT 119.175	PITTSBURGH APP CON 119.35 285.575	CLNC DEL 127.3	UNICOM 122.975 (CTAF) 0
----------------------------	---	--------------------------	-----------------------------------

ELEV 1184	TDZE 1184
------------------	------------------

1700

3300

HLG

VGSI and RNAV glidepath not coincident (VGSI Angle 3.09°/TCH 62).

4 NM Holding Pattern

ANUYE

KEYRE

3000

273°

093°

273°

6000

3000

GP 3.09° TCH 57

2.3 NM

3.1 NM

6.1 NM

CATEGORY	A	B	C	D
LPV DA		1386-¾	202 (300-¾)	
LNAV/VNAV DA		2140-4	956 (1000-4)	
LNAV MDA	1980-1 796 (800-1)	1980-1¼ 796 (800-1¼)	1980-2½ 796 (800-2½)	
CIRCLING	1980-1 796 (800-1)	2020-1¼ 836 (900-1¼)	2020-2½ 836 (900-2½)	2040-2¾ 856 (900-2¾)

HIRL Rwy 9-27 0

REIL Rwy 27 0