

WAAS CH 82215 W28A	APP CRS 277°	Rwy ldg 4971 TDZE 1134 Apt Elev 1136
--	------------------------	---


RNAV (GPS) RWY 28

WAYNE COUNTY (BJJ)


⚠ Baro-VNAV NA when using Akron-Canton Rgnl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). Helicopter visibility reduction below ¼ SM NA. When local altimeter setting not received, use Akron-Canton Rgnl altimeter setting: increase LPV DA to 1458 feet, LNAV/VNAV DA to 1649 feet, and visibility LPV all Cats ¼ SM and LNAV/VNAV all Cats ½ SM; increase all MDA 60 feet and visibility LNAV Cat C/D ½ SM and Circling Cat C/D ¼ SM.

MISSED APPROACH:
Climb to 3000 direct JAVNE and hold.

ASOS 118.075	CLEVELAND APP CON * 118.6 371.875	CLNC DEL 121.75	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------	---------------------------------



ELEV 1136	TDZE 1134
-----------	-----------



3000	JAVNE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 33).	6 NM Holding Pattern
*LNAV only	HENKO 2 NM to RWY 28	COMWE	DEHYH
RWY 28	1800*	2800	3000
2 NM	3.1 NM	6 NM	GP 3.00° TCH 35

CATEGORY	A	B	C	D
LPV DA	1398-1 264 (300-1)			
LNAV/ VNAV DA	1589-1½ 455 (500-1½)			
LNAV MDA	1560-1	426 (500-1)	1560-1¼	426 (500-1¼)
CIRCLING	1600-1 464 (500-1)	1700-1 564 (600-1)	1800-1¾ 664 (700-1¾)	1840-2¼ 704 (800-2¼)

REIL Rwy 10 and 28 0
HIRL Rwy 10-28 0

EC-2, 08 SEP 2022 to 06 OCT 2022

EC-2, 08 SEP 2022 to 06 OCT 2022