

WAAS CH 42801 W23A	APP CRS 229°	Rwy Idg TDZE Apt Elev	5898 13 13
--	------------------------	-----------------------------	---------------------------------------


RNAV (GPS) Y RWY 23
BOCA RATON (BCT)

RNP APCH.

T Rwy 23 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, procedure NA below -15°C or above 54°C. In minimum visibility conditions, bright lights on highway $\frac{1}{4}$ mile north of airport may be mistaken as runway lights.

MISSED APPROACH: Climb to 2100 direct TANAH and on track 297° to ATONE and hold

AWOS-3 121.125	PALM BEACH APP CON 127.35 343.6	BOCA RATON TOWER ★ 118.425 (CTAF) 0	GND CON 121.8	CLNC DEL 121.8	GCO 127.35
-------------------	------------------------------------	--	------------------	-------------------	---------------



2100 ↑	TANAH ✱	tr 297°	ATONE △	VGS1 and RNAV glidepath not coincident (VGS1 Angle 3.25/TCH 46).			
* LNAV only.				KISEC	4 NM Holding Pattern		
				GP 3.00° TCH 55			
CATEGORY		A		B		C	
LPV	DA	263-7 $\frac{1}{8}$ 250 (300-7 $\frac{1}{8}$)					
LNAV/ VNAV	DA	357-1 $\frac{1}{8}$ 344 (400-1 $\frac{1}{8}$)					
LNAV MDA		480-1 467 (500-1)				480-1 $\frac{3}{8}$ 467 (500-1 $\frac{3}{8}$)	
CIRCLING	2100	680-1 667 (700-1)				680-1 $\frac{3}{4}$ 667 (700-1 $\frac{3}{4}$)	
		680-1 667 (700-1)				880-2 $\frac{3}{4}$ 867 (900-2 $\frac{3}{4}$)	

