

LOC/DME I-OHN 108.9 Chan 26	APP CRS 360°	Rwy Idg 9320 TDZE 321 Apt Elev 341
---	------------------------	---

ILS or LOC RWY 36L
MEMPHIS INTL (MEM)



⚠ Simultaneous approach authorized with Rwy 36C/R.
⚠ For inoperative ALSF, increase S-ILS 36L Cat E visibility to RVR 4000, and S-LOC 36L Cat E visibility to 1½.
DME or RADAR required.

ALSF-2

MISSED APPROACH: Climb to 1000 then climbing left turn to 5000 via heading 330° and GQE VOR/DME R-121 to KALIE INT/GQE 15 DME and hold, continue climb-in-hold to 5000.

MEMPHIS APP CON			MEMPHIS TOWER		GND CON	
119.1	291.6	(176°-355°)	(Rwy 9-27)	118.3 257.8	(Rwy 9-27)	121.0 379.2
125.8	338.3	(356°-175°)	(Rwys 18C-36C, 18L-36R)	119.7 257.8	(Rwys 18C-36C, 18L-36R)	121.9 379.2
			(Rwy 18R-36L)	128.425 257.8	(Rwy 18R-36L)	121.65 379.2

D-ATIS 127.75	113.0 GQE Chan 77	1001	CLNC DEL 125.2	CPDLC
-------------------------	-----------------------------	-------------	---------------------------------	-------



1000 ↑	5000 hdg 330°	GQE R-121	KALIE △	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 73).		Procedure Turn NA
*LOC only.			CADUS I-OHN <u>6.7</u> RADAR	MACEE I-OHN <u>9.9</u> RADAR	FREA Z I-OHN <u>14</u> RADAR	
			2000	360°	4000	
			2000	3000	GS 3.00° TCH 59	
CATEGORY	A		B	C	D	E
S-ILS 36L	521/18 200 (200-½)				521/24 200 (200-½)	
S-LOC 36L	760/24 439 (500-½)		760/40 439 (500-¾)	760/50 439 (500-1)		
CIRCLING	940-1 599 (600-1)		940-1½ 599 (600-1½)	1020-2¼ 679 (700-2¼)	1140-2¾ 799 (800-2¾)	

SE-1, 01 DEC 2022 to 29 DEC 2022

SE-1, 01 DEC 2022 to 29 DEC 2022