

TOP ALTITUDE:
5000

8L-36R)

EMAXE

HOOSE

36L/C/R:
um climb
50.

or GPS required.

/C/R, 36L/C/R -
d for non-GPS
ft.
27 - RADAR required.
de will be issued via
s clearance delivery.
OK, reaching 10000 MSL,
or greater,
ATC.
ept climb rates, advise ATC
t.

PIEPE

IBUFY

NOTE: Chart not to scale

Rwy 9, 18L/C/R, 27, 36L/C/R:
Standard with minimum climb
of 500' per NM to 860.

- NOTE: DME/DME/IRU or GPS required.
NOTE: RNAV 1.
NOTE: Turbojets only.
NOTE: Takeoff Rwy 18L/C/R, 36L/C/R -
RADAR required for non-GPS
equipped aircraft.
NOTE: Takeoff Rwy 9, 27 - RADAR required.
NOTE: Transponder code will be issued via
PDC or Memphis clearance delivery.
NOTE: Accelerate to 250K, reaching 10000 MSL,
maintain 250K or greater,
if unable advise ATC.
NOTE: If unable to accept climb rates, advise ATC
on initial contact.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

SE-1, 01 DEC 2022 to 29 DEC 2022