

Procedure not authorized when tethered balloon located approximately 2 miles southeast of airport is flying. When local altimeter setting not received, use Currutuck altimeter setting and increase all MDA 40 feet.

SALS

A2

11

11

MISSED APPROACH: Climb to 1600 then left turn direct LLW NDB and hold.

ASOS 124.375	NORFOLK APP CON 119.55 269.425	ELIZABETH CITY TOWER★ 120.5 (CTAF) 355.6	GND CON 121.9	UNICOM 122.95
-----------------	-----------------------------------	---	------------------	------------------

RADAR required for procedure entry at SWOPE.

Remain within 10 NM

CATEGORY	A	B	C	D
S-10	640-1 629 (700-1)		640-1¾ 629 (700-1¾)	640-2 629 (700-2)
CIRCLING	640-1 629 (700-1)		640-1¾ 629 (700-1¾)	640-2 629 (700-2)

ELEV 11	TDZE 11
---------	---------

101° 5.5 NM from FAF

MIRL Rwy 1-19
HIRL Rwy 10-28
REIL Rws 10 and 28

Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

ELIZABETH CITY, NORTH CAROLINA

Orig-H 13AUG20

ELIZABETH CITY CG AIR STATION/RGNL (E/C/G)

36°16'N-76°10'W

NDB RWY 10

SE-2, 01 DEC 2022 to 29 DEC 2022

SE-2, 01 DEC 2022 to 29 DEC 2022