ILS or LOC RWY 20

CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

LOC/DME I-LHJ	APP CRS	Rwy Idg	8000
111.55	201°	TDZE	871
Chan 52 (Y)		Apt Elev	871

VDP NA when using General Downing-Peoria Intl altimeter setting. When local altimeter setting not received, use General Downing-Peoria Intl altimeter setting: increase all DA 116 feet and all MDA 120 feet; increase S-ILS all Cats visibility to RVR 2400, S-LOC Cat C and D visibility to RVR 5500, and Circling Cat C and D visibility ¼ mile. For inoperative ALSF-2 when using General Downing-Peoria Intl altimeter setting increase ILS all Cats visibility to RVR 5000.

ALSF-2

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 on heading 270° and PNT VOR/DME R-214 to MCLEN INT/PNT 31 DME and hold.

ATIS	SAINT LOUIS APP CON	BLOOMINGTON TOWER ★	GND CON	UNICOM
135.35	128.725 256.9	124.6 (CTAF) L 269.575	121.65	122.95

ALTERNATE MISSED APCH FIX
LOM EGROW
334 LH

IAF PONTIAC
109.6 PNT
Chan 33

2500 NoPT
202° (10.7)

1787

R-277

116.8 RBS
Chan 115

(IF)
OLIDE INT
I-LHJ 10.9

BLOOMINGTON
108.2 BMI
Chan 19

LOM/IAF EGROW
334 LH
I-LHJ 4.6

PNT R-214

MSA LH 25 NM
2800

996±
961±
1021
IM
1210
1220
996
1256
1301

LOCALIZER 111.55
I-LHJ
Chan 52 (Y)

MCLEN
PNT 31

115.2 PIA
Chan 99

R-242
034°
214°
R-115

ELEV 871 D TDZE 871
201° 4.8 NM from FAF
916
917±
6525 X 150
8000 X 150
TWR
972

TDZ/CL Rwy 20 L
HIRL Rwys 2-20 and 11-29 L

1500 | 3000 hdg 270° | PNT R-214 | MCLEN | LH LOM I-LHJ 4.6

Remain within 10 NM

* LOC only
*I-LHJ 0.9
IM
2459
021°
201°
2500
2500
GS 3.00°
TCH 58
0.2 0.9 3.7 NM

CATEGORY	A	B	C	D
S-ILS 20	1071/18 200 (200-½)			
S-LOC 20	1260/24 389 (400-½)		1260/35 389 (400-⅝)	
C CIRCLING	1340-1 469 (500-1)		1620-2¼ 749 (800-2¼)	1620-2½ 749 (800-2½)

FAF to MAP 4.8 NM

Knots	60	90	120	150	180
Min:Sec	4:48	3:12	2:24	1:55	1:36

EC-3, 01 DEC 2022 to 29 DEC 2022
EC-3, 01 DEC 2022 to 29 DEC 2022