

WAAS CH 77602 W24A	APP CRS 242°	Rwy ldg TDZE Apt Elev	5280 2684 2684
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 24

LONESOME PINE (LNP)

RNP APCH.

⚠

Circling to Rwy 6 NA at night. Rwy 24 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. Inop table does not apply to LPV all Cats and LNAV Cats A/B. For inop ALS, increase LNAV/VNAV Cat A/B visibility to 1½ SM and LNAV Cat C/D visibility to 1¾ SM.

ODALS

.....

MISSED APPROACH:
Climb to 6400 direct HOGIB and on track 271° to FLENR and hold, continue climb-in-hold to 6400.

AWOS-3 118.6	INDIANAPOLIS CENTER 126.575 253.5	UNICOM 123.0 (CTAF) 0
------------------------	---	---------------------------------

ELEV 2684 TDZE 2684

REIL Rwy 6 0
MIRL Rwy 6-24 0

6400	HOGIB	tr 271°	FLENR	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 36).	5 NM Holding Pattern
*LNAV only				JUBTO	
*1.6 NM to RWY 24				GP 3.00° TCH 55	
RWY 24				8000 5400	
1.6 NM 3.3 NM 6.8 NM				062° 242°	
CATEGORY	A	B	C	D	
LPV DA	2962-1		278 (300-1)		
LNAV/VNAV DA	3112-1½		428 (500-1½)		
LNAV MDA	3140-1		3140-1½		456 (500-1½)
CIRCLING	3240-1	3360-1	3360-2	3560-2¾	
	556 (600-1)	676 (700-1)	676 (700-2)	876 (900-2¾)	

WISE, VIRGINIA
Amdt 1 25FEB21

36°59'N-82°32'W

LONESOME PINE (LNP)
RNAV (GPS) RWY 24