

When local altimeter setting not received, use Vernal altimeter setting and increase all MDA 80 feet, FOSLA fix minimums, increase Cat C visibility ¼ SM.

MISSED APPROACH: Climbing right turn to 9000 direct MTU VOR/DME and hold, continue climb-in-hold to 9000.

AWOS-3P 118.975	SALT LAKE CENTER 135.77 257.7	UNICOM 122.8 (CTAF) 0
--------------------	----------------------------------	--------------------------

Diagram illustrating the approach route to Roosevelt Muni (74V). The route starts at the Initial Approach Fix (IAF) MYTON (112.7 MTU, Chan 74). The route proceeds via the FOSLA fix (5.2 NM) and the MARPK fix (8.2 NM). Key altitudes and distances are marked: 5557, 5502±, 5857, 5474, 5593, 5206, 5323, 5418, 6268, 6280, 5176. The route includes a 160° turn and a 340° turn. A 1-minute climb-in-hold is indicated. A 160° turn is also shown at the bottom left. A circular inset shows the MSA MTU 25 NM with altitudes 11900 and 7800, and angles 220° and 310°.

One Minute Holding Pattern				9000	MTU
8500 ← 160° → 340°					
MTU VOR/DME				FOSLA MTU 5.2	MARPK MTU 8.2
6280				5.2 NM	3 NM
CATEGORY	A	B	C	D	
CIRCLING	6280-1¼ 1104 (1200-1¼)	6280-1½ 1104 (1200-1½)	6280-3 1104 (1200-3)	6340-3 1164 (1200-3)	
FOSLA FIX MINIMUMS					FAF to MAP 8.2 NM
CIRCLING	5760-1 584 (600-1)	5900-1 724 (800-1)	6020-2½ 844 (900-2½)	6340-3 1164 (1200-3)	Knots Min:Sec 8:12 5:28 4:06 3:17 2:44

ELEV 5176

6501 X.75

1.0% UP

010° 8.2 NM from FAF

MIRL Rwy 7-25 0

REIL Rwy 7 and 25 0

ROOSEVELT, UTAH

Amtd 4 10NOV16

40°17'N-110°03'W

ROOSEVELT MUNI (74V)

VOR-A