


WAAS CH 93544 W04A	APP CRS 038°	Rwy ldg TDZE Apt Elev	4870 1240 1243
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 4R
CHANDLER MUNI (CHD)

RNP APCH - GPS. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C.		MISSED APPROACH: (Do not exceed 210K until DECTU) Climb to 2200 then climbing right turn to 4000 direct to DECTU and hold.	
ATIS 128.325	PHOENIX APP CON 123.7 363.0	CHANDLER TOWER ★ 126.1 (CTAF) 0 133.1 (North and West) (South and East)	GND CON 124.4 UNICOM 122.95



DECTU				
4000				
GP 3.00° TCH 39				
DECTU				
KEDDU				
2900				
2900				
RW04R				
1.1 NM to RW04R				
5.2 NM				
4 NM				
1.1 NM				
CATEGORY	A	B	C	D
LPV DA	1490-3/4	250 (300-3/4)		NA
LNAV/VNAV DA	1640-1 1/8	400 (400-1 1/8)		NA
LNAV MDA	1640-1	400 (400-1)	1640-1 1/8 400 (400-1 1/8)	NA
CIRCLING	1700-1 457 (500-1)	1760-1 517 (600-1)	1760-1 1/2 517 (600-1 1/2)	NA

