

WAAS CH 90326 W34A	APP CRS 344°	Rwy Idg 3502 TDZE 1279 Apt Elev 1279
--	------------------------	---

RNAV (GPS) RWY 34

FOSSTON MUNI/ANDERSON FLD (FSE)

RNP APCH.

T VDP NA when using Thief River Falls altimeter setting. When local altimeter setting not received, use Thief River Falls altimeter setting and increase all MDA 100 feet and increase **A** LP and LNAV Cat C visibility $\frac{3}{8}$ SM, and increase Circling Cat C visibility $\frac{1}{2}$ SM.

MISSED APPROACH:
Climb to 4000 direct
ZOBON and hold.

AWOS-3 118.35	MINNEAPOLIS CENTER 134.75 251.1	GCO 121.725	CTAF 122.9 0
-------------------------	---	-----------------------	------------------------




Diagram illustrating the 16-34 approach procedure. The runway is 3.607 NM x 75 ft, with a 0.4% up-slope. The approach is a 344° climb. Key points include RW34 at 1.1 NM, WEXEL at 2.8 NM, and SPODA at 4 NM. The diagram also shows the 3100 and 2200 MSL altitudes and the 3.00° TCH 40° angle.

CATEGORY	A	B	C	D
LP MDA	1620-1	341 (400-1)		NA
LNAV MDA	1760-1	481 (500-1)	1760-1 ³ / ₈ 481 (500-1 ³ / ₈)	NA
CIRCLING	1860-1	581 (600-1)	1860-1 ¹ / ₂ 581 (600-1 ¹ / ₂)	NA

