

WAAS CH 65700 W27A	APP CRS 275°	Rwy Idg TDZE 999 Apt Elev 1026
--	------------------------	--



RNAV (GPS) RWY 27L
HARTSFIELD-JACKSON ATLANTA INTL (ATL)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized with Rwy 26R or 26L. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSIF-2

MISSED APPROACH: Climb to 4000 direct CALUP and on track 272° to TEMPO and hold.

D-ATIS ARR 119.65 DEP 125.55	ATLANTA APP CON 127.9 379.9	ATLANTA TOWER 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS 119.1 125.325 123.85 119.3 119.5 254.4						ALL RWYS 121.9		GND CON (8L-26R,8R-26L) (9L-27R,9R-27L) 10-28 RWYS 121.75 121.65 254.4	
--	--	--	--	--	--	--	--	-----------------------------	--	---	--



RADAR REQUIRED			
4000	CALUP	tr 272°	TEMPO
VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 79).			
*LNAV only.			
*1.7 NM to RWY 27L			
RWY 27L			
DEPOT			
GRMPI			
SEJAY			
ROMMM			
SLVAA			
7000			
GP 3.00° TCH 58			
1.7 NM 3.8 NM 4.7 NM 3.8 NM 3.5 NM 3.5 NM			
CATEGORY	A	B	C
LPV DA	1199/18 200 (200-½)		
LNAV/VNAV DA	1528-1⅓ 529 (600-1⅓)		
LNAV MDA	1620/24 621 (600-½) 1620-1⅓ 621 (600-1⅓)		

SE-4, 26 JAN 2023 to 23 FEB 2023

SE-4, 26 JAN 2023 to 23 FEB 2023