

WAAS CH 42939 W22B	APP CRS 213°	Rwy Idg TDZE Apt Elev	10000 642 645
--	------------------------	-----------------------------	--

RNAV (GPS) Y RWY 22R
DETROIT METRO WAYNE COUNTY (DTW)



⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 1100 then climbing right turn to 4000 direct DOHNT and hold.

D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 135.0 317.725	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)	CLNC DEL 120.65	CPDLC
--------------------------	--	-------------------------------------	---	---------------------------	-------

RADAR REQUIRED



1100	4000	DOHNT	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).						
			TAYUL MMOTR GRDCY						
*LNAV only.									
			GP 3.00° TCH 55						
CATEGORY		A		B		C		D	
LPV DA				892/24		250 (300-½)			
LNAV/ VNAV DA				1050/45		408 (500-¾)			
LNAV MDA		1060/24		418 (500-½)		1060/40		418 (500-¾)	
C CIRCLING		1180-1		535 (600-1)		1180-1½ 535 (600-1½)		1240-2 595 (600-2)	

EC-1, 26 JAN 2023 to 23 FEB 2023

EC-1, 26 JAN 2023 to 23 FEB 2023