

WAAS
CH **53528**
W18A

APP CRS
180°

Rwy Idg **5199**
TDZE **430**
Apt Elev **430**


RNAV (GPS) RWY 18

LAWRENCEVILLE-VINCENNES INTL (L WV)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 41°C (105°F).
⚠ DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Mount Carmel altimeter setting. When local altimeter setting not received, use Mount Carmel altimeter setting: increase LPV DA 656 feet; increase LNAV/VNAV DA to 902 feet and all visibilities ½ SM; increase all MDAs 40 feet and LNAV visibility Cat C/D ¼ SM; and Circling visibility Cat D ¼ SM. Circling to Rwy 36 NA at night.

MISSED APPROACH:
Climb to 2600 direct
VOCUT and hold.

ASOS 118.0	EVANSVILLE APP CON ★ 125.6 343.7	UNICOM 122.8 (CTAF) ①
----------------------	--	---------------------------------



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 25).		2600	VOCUT
2600		180°		180°	*LNAV only.
GP 3.00° TCH 45		2100		2100	
		6.8 NM		3.2 NM	1.9 NM
CATEGORY	A	B	C	D	
LPV DA	630-¾		200 (200-¾)		
LNAV/VNAV DA	876-1½		446 (500-1½)		
LNAV MDA	940-1	510 (600-1)	940-1¾	510 (600-1¾)	
CIRCLING	940-1	510 (600-1)	940-1½	1160-2¼	730 (800-2¼)

