VOR RWY 35
AINSWORTH RGNL (ANW)

VOR/DME ANW 112.7 Chan 74	APP CRS 008°	Rwy ldg 6824 TDZE 2589 Apt Elev 2589

When local altimeter setting not received, procedure NA.
For inoperative ALS, increase BIYAG fix minimums S-35 Cat D visibility to 1¼.

MALSR

MISSED APPROACH: Climb to 3500 then climbing left turn to 6000 direct ANW VOR/DME and hold.

AWOS-3	DENVER CENTER	UNICOM
118.325	127.95 338.2	122.8 (CTAF) L





CATEGORY	A	B	C	D
S-35	3300-½ 711 (800-½)		3300-1½ 711 (800-1½)	3300-1¾ 711 (800-1¾)
C CIRCLING	3300-1 711 (800-1)		3300-2 711 (800-2)	3300-2¼ 711 (800-2¼)
BIYAG FIX MINIMUMS (DME REQUIRED)				
S-35	3000-½ 411 (500-½)		3000-¾ 411 (500-¾)	3000-1 411 (500-1)
C CIRCLING	3000-1 411 (500-1)	3040-1 451 (500-1)	3040-1½ 451 (500-1½)	3200-2 611 (700-2)

ELEV 2589	TDZE 2589

HIRL Rwys 13-31 and 17-35 L
REIL Rwy 31 L



NC-2, 26 JAN 2023 to 23 FEB 2023
NC-2, 26 JAN 2023 to 23 FEB 2023