

LOC/DME I-SVH
111.75
Chan **54** (Y)

APP CRS
285°

Rwy Idg
TDZE **967**
Apt Elev **968**

ILS Z or LOC Z RWY 28

STATESVILLE RGNL (SVH)

When local altimeter setting not received, use Lincolnton altimeter setting and increase ILS DA to 1219 and all MDA 60 feet; increase S-LOC 28 Cats C/D visibility ⅓ mile and Circling Cat C visibility ¼ mile. VDP NA when using Lincolnton altimeter setting. For inop MALSR when using Lincolnton altimeter setting, increase S-ILS 28 all Cats visibility to ⅔ mile and S-LOC 28 Cats C/D visibility to 1 mile. DME required.

MALSR
AS

MISSED APPROACH: Climb to 1700 then climbing left turn to 3400 on heading 105° and CLT VOR/DME R-025 to PEGTE INT/I-SVH 13.2 DME and hold.

AWOS-3 119.225	ATLANTA CENTER 125.15 263.0	UNICOM 123.075 (CTAF) 1
--------------------------	---------------------------------------	--

ELEV 968	D	TDZE 967	1700	3400	CLT R-025	PEGTE	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 50).	One Minute Holding Pattern
		hdg 105°				HESAB I-SVH 6.2	PEGTE I-SVH 13.2	
		*LOC only.				ICENU I-SVH 3.6		
		*I-SVH 1.2				*I-SVH 2		
		2600				2600		
		*1760						
		0.8				1.6	2.6 NM	
						7 NM		
CATEGORY	A		B		C		D	
S-ILS 28	1167-½		200 (200-½)					
S-LOC 28	1280-½		313 (400-½)					
CIRCLING	1420-1 452 (500-1)		1540-1 572 (600-1)		1540-1½ 572 (600-1½)		1560-2 592 (600-2)	

STATESVILLE, NORTH CAROLINA
Amdt 1A 12OCT17

35°46'N-80°57'W

STATESVILLE RGNL (SVH)
ILS Z or LOC Z RWY 28