

WAAS CH 61335 W35A	APP CRS 348°	Rwy Idg TDZE 927 Apt Elev 936	5002
--	------------------------	---	-------------

RNAV (GPS) RWY 35

LAWRENCEBURG-LAWRENCE COUNTY (2M2)


▼

▲NA

Circling Rwy 17 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Huntsville Intl-Carl T Jones Fld altimeter setting and increase all DA 142 feet and all MDA 140 feet; increase LPV all Cats visibility ¼ mile, LNAV/VNAV all Cats visibility ⅓ mile. Rwy 17 helicopter visibility reduction below 1 SM NA. Rwy 35 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 3700 direct WABOL and hold.

AWOS-3 120.175	MEMPHIS CENTER 125.85 379.25	UNICOM 122.8 (CTAF)
--------------------------	--	-------------------------------



ELEV 936

TDZE 927

1118

★

L1

5002 x 100

35

348° to RW35

MIRL Rwy 17-35

REIL Rws 17 and 35

3700

WABOL

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 50).

4 NM Holding Pattern

*LNAV only.

YITUT

JOMVU
2.4 NM to RW35

RW35

1800

2600

348°

168°

3800

GP 3.20°
TCH 60

CATEGORY	A	B	C	D
LPV DA	1293-1⅛	366 (400-1⅛)		NA
LNAV/VNAV DA	1354-1¼	427 (500-1¼)		NA
LNAV MDA	1340-1	413 (500-1)		NA
CIRCLING	1500-1	564 (600-1)		NA