

WAAS CH 53410 W10A	APP CRS 104°	Rwy Idg TDZE 6591 Apt Elev 6606
--	------------------------	---

RNAV (GPS) Y RWY 10

YAMPA VALLEY (HDN)

RNP APCH-GPS. ⚠ Rwy 10 helicopter visibility reduction below ¾ SM NA. ⚠ Inop table does not apply to *LPV all Cats, LNAV/VNAV all Cats, and LNAV Cats C/D. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -28°C or above 54°C.	MALSF 	MISSED APPROACH: Climb to 13700 direct OBTUE and on track 124° to TILLI and hold, continue climb-in-hold to 13700. * Missed approach requires minimum climb of 295 feet per NM to 8700.
---	-----------	--

AWOS-3 119.275	DENVER CENTER 120.475 235.975	UNICOM 123.0 (CTAF) 0
--------------------------	---	---------------------------------



ELEV 6606	D	TDZE 6591
-----------	----------	-----------

		REVME		13700	OBTUE	tr 124°	TILLI
7 NM Holding Pattern		INEDE		8700		3.5 NM to RWY 10	
14000 ← 284°		10000 → 104°		8700		RWY 10	
GP 3.00°		TCH 55		6.8 NM		3 NM	
CATEGORY		A		B		C	
LPV DA*		6791-¾		200 (200-¾)			
LPV DA		7327-1¾		736 (800-1¾)			
LNAV/VNAV DA		7966-5		1375 (1400-5)			
LNAV MDA		7760-1		7760-1¼		7760-3	
		1169 (1200-1)		1169 (1200-1¼)		1169 (1200-3)	
CIRCLING		7760-1¼		7760-1½		7760-3	
		1154 (1200-1¼)		1154 (1200-1½)		1154 (1200-3)	
						8180-3	
						1574 (1600-3)	