

APP CRS	Rwy Idg	4000
354°	TDZE	984
	Apf Elev	985

RNAV (GPS) RWY 35

CHANDLER RGNL (CQB)

RNP APCH.

▼

▲ NA

When local altimeter setting not received, use Shawnee altimeter setting and increase all MDA 80 feet; increase LNAV Cat C visibility ½ SM. VDP NA with Shawnee Rgnl altimeter setting.

MISSED APPROACH: Climb to 2600 direct CADUT and hold.

AWOS-3PT
119.275

KANSAS CITY CENTER
127.8 319.1

CTAF
122.9 0

▲1553

1459
1459
1459

1160
RW35

▲1293

30 NM to FEDAL

10 NM to FEDAL

FEDAL

3800

2600

084°

174°

30 NM to EPASE

EPASE

2600

174°

264°

(IAF) FEDAL

2600 NoPT

084°

(5)

(IF/IAF) CALKI

2600 NoPT

264°

(5)

(IAF) EPASE

354°

174°

4 NM

084°

264°

5 NM to CALKI (NoPT)

2600

3100

30 NM to CALKI

ELEV 985

TDZE 984

35

4000 X 60

0.6% Up

354° to RW35

MIRL Rwy 17-35 0

2600

CADUT

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 42).

*LNAV only.

*1.1 NM to RW35

UBIRY

CALKI

4 NM Holding Pattern

354°

174°

2600

GP 3.00° TCH 30

1.1

3.8 NM

5 NM

CATEGORY	A	B	C	D
GLS PA DA	NA			
LNAV/VNAV DA	NA			
LNAV MDA	1320-1 335 (400-1)		NA	

CHANDLER, OKLAHOMA
Orig-B 15AUG19

35°43'N-96°49'W

CHANDLER RGNL (CQB)

RNAV (GPS) RWY 35

SC-1, 26 JAN 2023 to 23 FEB 2023

SC-1, 26 JAN 2023 to 23 FEB 2023