

WAAS CH 40313 W01B	APP CRS 006°	Rwy Idg TDZE 17 Apt Elev 36	5930
--	------------------------	---	-------------

RNAV (GPS) Z RWY 1L

NAPA COUNTY (APC)

RNP APCH-GPS.



▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 54°C. Inop table does not apply to LPV minimums. For inop ALS, increase visibility LNAV/VNAV to ½ SM. Missed approach requires minimum climb of 420 feet per NM to 2200. If unable to meet climb gradient see RNAV (GPS) Y RWY 1L.


MALS

MISSED APPROACH: Climb to 5000 direct CIVDA and on track 326° to POPES and hold, continue climb-in-hold to 5000.

ATIS 124.05	OAKLAND CENTER 127.8 353.5	NAPA TOWER ★ 118.7 (CTAF) 0 257.8	GND CON 121.7	CLNC DEL 127.85	UNICOM 122.95
-----------------------	--------------------------------------	---	-------------------------	---------------------------	-------------------------



CATEGORY	A	B	C	D
LPV DA		217-¾ 200 (200-¾)		
LNAV/VNAV DA		330-¾ 313 (300-¾)		
LNAV MDA	560-¾ 543 (600-¾)		560-1¾ 543 (600-1¾)	



SW-2, 23 FEB 2023 to 23 MAR 2023

SW-2, 23 FEB 2023 to 23 MAR 2023