

WAAS CH 78335 W14A	APP CRS 143°	Rwy Idg 4400 TDZE 1798 Apt Elev 1800
--	------------------------	---

RNAV (GPS) RWY 14

SMITH CENTER MUNI (K82)

RNP APCH-GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. When local altimeter setting not received, use Concordia altimeter setting and increase all DA 169 feet and all MDA 180 feet; increase LPV all Cats visibility ¼ SM, LNAV/VNAV all Cats visibility ½ SM, Circling Cat A visibility ¼ SM and Circling Cat B visibility ½ SM. Baro-VNAV and VDP NA with Concordia altimeter setting. Circling Rwy 36 NA at night.

MISSED APPROACH:
Climb to 3700 direct JUXUL and hold.

AWOS-3PT
118.45

MINNEAPOLIS CENTER
119.4 278.8

UNICOM
122.8 (CTAF) 0

4 NM

323°

143°

(IF/IAF) LAYIP

3700 (6.2)

143°

(FAF) WONID

Λ 2236

Λ 2141

RW14

Λ 1840

30 NM to LAYIP (NoPT)

3900

233°

LAYIP

233°

LAYIP

053°

053°

30 NM to LAYIP

3900

2261 Λ

MISSED APCH FIX

JUXUL

143°

323°

4 NM

4 NM Holding Pattern

LAYIP

3700

323°

143°

143°

3700

WONID

3700

*1.6 NM to RW14

RW14

*LNAV only.

GP 3.00°

TCH 40

6.2 NM

4.3 NM

1.6 NM

ELEV 1800

D

TDZE 1798

143° to RW14

0.38° UP

81

50 X 1095

400 X 75

32

36

0.38° UP

MIRL Rwy 14-32 0

REIL Rws 14 and 32 0

CATEGORY	A	B	C	D
LPV DA	1998-1	200 (200-1)		NA
LNAV/VNAV DA	2076-1	278 (300-1)		NA
LNAV MDA	2320-1	522 (600-1)		NA
CIRCLING	2480-1 680 (700-1)	2580-1 780 (800-1)		NA

NC-2, 23 FEB 2023 to 23 MAR 2023

NC-2, 23 FEB 2023 to 23 MAR 2023