

APP CRS	Rwy Idg	8000
201°	TDZE	551
	Apt Elev	599

RNAV (RNP) Z RWY 20L


NASHVILLE INTL (BNA)

GPS required. Simultaneous approach authorized with Rwy 20R. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -11°C (13°F) or above 54°C (130°F). Inop table does not apply to RNP 0.20. For inop MALSR, increase RNP 0.30 all Cats visibility to 1½.

MALSR

MISSED APPROACH: Climb to 1300 then climbing left turn to 4000 direct CENOP and hold.

D-ATIS 135.1	NASHVILLE APP CON 118.4 360.7	NASHVILLE TOWER 118.6 257.8	GND CON 121.9 348.6	CLNC DEL 126.05	CPDLC
------------------------	---	---------------------------------------	-------------------------------	---------------------------	-------



ELEV 599	D TDZE 551
----------	-------------------

MISSED APCH FIX

CENOP

RADAR REQUIRED

See planview for multiple IF locations.

GP 3.00°
TCH 47'

CATEGORY	A	B	C	D
RNP 0.20 DA	810/40	259 (200-¾)		
RNP 0.30 DA	1008/55	457 (400-1)		

AUTHORIZATION REQUIRED

HIRL all Rwys
TDZ/CL Rwys 2L and 2R
REIL Rwys 13, 20C, and 31

SE-1, 23 MAR 2023 to 20 APR 2023

SE-1, 23 MAR 2023 to 20 APR 2023