
KRMSN FOUR DEPARTURE (RNAV)



1800

1800

OKLAHOMA CITY, OKLAHOMA
D-ATIS
125.85

125.85 CLNC DEL 124.35 GND CON 121.9 348.6 ROGERS TOWER 119.35 269.45 OKE CITY DEP CON 124.2 336.4

20 APR 2023

SC-1, 23 MAR 2023

NOTE: RADAR required.


NOTE: DME/DME/IRU or GPS required.

NOTE: RNAV 1.

TAKEOFF MINIMUMS

1800-

Rwys 13, 17L/R, 18, 31, 35L/R, 36: Standard with minimum climb of 500' per NM to 1800.



NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

<u>TAKEOFF RUNWAY 13:</u> Climb on heading 131° to 1800, then right turn heading 176° or as assigned by ATC, expect RADAR vectors to cross SWTZR at or above 4200, thence...

TAKEOFF RUNWAYS 17L/R, 18: Climb on heading 176° to 1800, then heading 176° or as assigned by ATC, expect RADAR vectors to cross SWTZR at or above 4200, thence...

<u>TAKEOFF RUNWAY 31:</u> Climb on heading 311° to 1800, then right turn heading 011° or as assigned by ATC, expect RADAR vectors to cross SWTZR at or above 4200, thence...

TAKEOFF RUNWAYS 35L/R, 36: Climb on heading 356° to 1800, then right turn heading 011° or as assigned by ATC, expect RADAR vectors to cross SWTZR at or above 4200, thence...

.... on track 136° to KRMSN, then on (transition). Maintain ATC assigned altitude. Expect filed altitude 10 minutes after departure.

WICKS TRANSITION (KRMSN4.WICKS)