RNAV (RNP) Z RWY 17L

WILL ROGERS WORLD (OKC)

APP CRS	Rwy Idg	TDZE	Apt Elev
176°	9802	1287	1296

ASR

For uncompensated Baro-VNAV systems, procedure NA below -12°C (11°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized with Rwy 17R. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 5000 on track 176° to JAVXE and hold, continue climb-in-hold to 5000.

D-ATIS	OKE CITY APP CON	ROGERS TOWER	GND CON	CLNC DEL
125.85	124.6 266.8	119.35 269.45	121.9 348.6	124.35

RADAR required for procedure entry at ATREC.

(IAF) ATREC (RNP 0.40) 5000

4000 176° (3.5)

(IF) GOLFS 210K

3000 176° (3.9)

HAMDO

WUVMA 210K

RADAR required for procedure entry at HIPES.

(IF) HIPES (RF Required) (RNP 0.80) 5000

3500 266° (5)

3000 (1.7)

SIWHU

2300 176° (2.3)

2300 (2.2)

2046

3500 (3.9)

ISAKE

(FAF) SCORY

176° (3)

4700 356° (4.1)

RW17L

1608

1416

1881

1953

(IF) PALMR (RF Required) (RNP 0.80) 6000 210K

(IF) FLAPP (RF Required) (RNP 0.40) 5000 210K

4000 086° (4.9)

4000 086° (0.8)

3500 (1.6)

MERTE

JINTA

DONMO

3000 (2.3)

4000 (4)

ADWOW

5000 356° (3.3)

(IF) WWILL (RF Required) (RNP 0.40) 6000 210K

MSA RW17L 25 NM

3800

2758

MISSED APCH FIX JAVXE

356° 176° 5 NM

176° (14.3)

ELEV 1296 D TDZE 1287

176°

17R 17L

TWR 1436

13 31 18 36

7800 X 150

3078 X 75

9801 X 150

9803 X 150

0.3%up

1340

35L 35R

REIL Rwys 13 and 31
TDZ/CL Rwy 35R
MIRL Rwy 13-31
HIRL Rwys 17L-35R and 17R-35L

5000 tr 176° JAVXE

See planview for multiple IF locations.

SCORY 2300

RW17L 176° 2300

GP 3.00° TCH 59

3 NM

CATEGORY	A	B	C	D
RNP 0.11 DA	1555/24 268 (300-½)			
RNP 0.20 DA	1643/34 356 (400-⅝)			
RNP 0.30 DA	1724/49 437 (500-1)			

AUTHORIZATION REQUIRED

SC-1, 23 MAR 2023 to 20 APR 2023
SC-1, 23 MAR 2023 to 20 APR 2023