

WAAS CH 61013 W30A	APP CRS 304°	Rwy Idg 4999 TDZE 9 Apt Elev 9
--	------------------------	---

RNAV (GPS) RWY 30

HOUMA-TERREBONNE (HUM)



▼

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting: increase LPV DA to 336, LNAV/VNAV DA to 489, and all visibilities ¼ SM; increase all MDAs 80 feet and visibility Cats C and D ⅜ SM. Baro-VNAV NA when using Louis Armstrong New Orleans Intl altimeter setting.

MISSED APPROACH: Climb to 1800 direct NACIV and hold.

ATIS 120.25	NEW ORLEANS APP CON 118.9 350.35	HOUMA TOWER★ 125.3 (CTAF) 0 346.3	GND CON 123.875	CLNC DEL 118.9 (When twr closed)	UNICOM 122.95
-----------------------	--	---	---------------------------	---	-------------------------



1800 NACIV		VGSi and RNAV glidepath not coincident (VGSi Angle 3.00°/TCH 39°).		4 NM Holding Pattern
* LNAV only		KEBCE 1.6 NM to RW30	RECYO	HOVPU
RW30		560*	304°	124° 1800
1.6 NM		3.8 NM	6 NM	GP 3.00° TCH 45
CATEGORY	A	B	C	D
LPV DA	259-¾ 250 (300-¾)			
LNAV/VNAV DA	412-1½ 403 (500-1½)			
LNAV MDA	380-1 371 (400-1)			
CIRCLING	480-1	471 (500-1)	760-2¼ 751 (800-2¼)	760-2½ 751 (800-2½)