

AWOS-3
119.475
CTAF
123.05
DETROIT DEP CON
132.35 284.0

**TOP ALTITUDE:
ASSIGNED BY ATC**

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 9: Climb on heading 096° to 1400 then as assigned for
RADAR vectors to cross JWELS at or above 4000, thence...
TAKEOFF RUNWAY 27: Climb on heading 276° to 1500 then as assigned for
RADAR vectors to cross JWELS at or above 4000, thence...

.....on track 218° to SNDRS, then on (transition). Maintain ATC assigned altitude, expect filed altitude 10 minutes after departure.

BGHRT TRANSITION (SNDRS2.BGHRT):

TORRR TRANSITION (SNDRS2.TORRR):

NOTE: RNAV 1.

NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: Turbojet departures at/above 10000,

maintain 280K until advised by ATC.



NOTE: TORRR TRANSITION: For use by KIND and KCVG area arrivals only and flights filed at or below FL220, or as assigned by ATC.

TAKEOFF MINIMUMS:

Rwy 9: Standard.

Rwy 27: Standard with minimum climb of 476' per NM to 1500.

NOTE: Chart not to scale.



SNDRS TWO DEPARTURE (RNAV)

(SNDRS2.SNDRS) 15AUG19

TROY, MICHIGAN

OAKLAND/TROY (VLL)