TROY, MICHIGAN **TOP ALTITUDE:** AWOS-3 **GNZOE** 119.475 **ASSIGNED BY ATC CTAF** 123.05 DETROIT DEP CON 132.35 284.0 DDEEZ **TRMML** TAKEOFF MINIMUMS: Rwy 9: Standard. Rwy 27: Standard with minimum climb of 476' per NM to 1500. LOALA 4000 096° 1500 1400 NOTE: RNAV 1. NOTE: RADAR required. NOTE: DME/DME/IRU or GPS required. NOTE: Turbojet departures at/above 10000, maintain 280K until advised by ATC.

V

23 MAR 2023

ಠ

20 APR 2023

## DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 9: Climb on heading 096° to 1400 then as assigned for RADAR vectors to cross LOALA at or above 4000, thence.... TAKEOFF RUNWAY 27: Climb on heading 276° to 1500 then as assigned for RADAR vectors to cross LOALA at or above 4000, thence....

....on track 352° to TRMML, then on (transition). Maintain ATC assigned altitude, expect filed altitude 10 minutes after departure.

GNZOE TRANSITION (TRMML3.GNZOE):

NOTE: Chart not to scale.