

WAAS

CH **45905**

W22A

APP CRS

215°

Rwy Idg

7193

TDZE

26

Apt Elev

26

RNAV (GPS) RWY 22

PUNTA GORDA (PGD)

▼

Baro-VNAV NA when using Page Fld altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 1°C or above 54°C. When local altimeter setting not received, use Page Fld altimeter setting and increase LPV DA to 276, LNAV/VNAV DA to 360, and all MDAs 60 feet; increase LNAV Cats C and D visibility ¼ SM, and Circling Cats C and D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 direct BULOW and hold.

ATIS ★ 135.675	FORT MYERS APP CON ★ 127.05 306.2	PUNTA GORDA TOWER ★ 121.0 (CTAF) 0	GND CON 119.55	CLNC DEL 119.55	CLNC DEL 127.05 (When twr closed)	UNICOM 122.975
--------------------------	---	--	--------------------------	---------------------------	--	--------------------------

ELEV 26	TDZE 26
215°	
2000 BULOW	
VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 31).	
*LNAV only.	
EGOTE 1.5 NM to RW22	
DOGLE 1600	
AIRVA 2000	
GP 3.00° TCH 40	
1.5 NM 3.3 NM 6 NM	
CATEGORY	A B C D
LPV DA	226-3/4 200 (200-3/4)
LNAV/VNAV DA	310-1 284 (300-1)
LNAV MDA	420-1 394 (400-1) 420-1 3/8 394 (400-1 1/8)
CIRCLING	460-1 434 (500-1) 580-1 554 (600-1) 600-1 574 (600-1 1/2) 740-2 714 (800-2 1/4)

PUNTA GORDA, FLORIDA

Amdt 2A 30JAN20

26°55'N-81°59'W

PUNTA GORDA (PGD)

RNAV (GPS) RWY 22