

# KLAWOCK ONE DEPARTURE (OBSTACLE) (RNAV)


ANCHORAGE CENTER  
118.5 284.6

RNAV 1 - GPS.

### TAKEOFF MINIMUMS

Rwy 2: NA - Obstacles.

Rwy 20: Standard with a minimum climb  
of 250' per NM to 4200.



### TAKEOFF OBSTACLE NOTES

- Rwy 20: Lighting beginning 1' from DER, 34' left of centerline, up to 2' AGL/40' MSL.
- Lighting 2' from DER, 54' right of centerline, 2' AGL/40' MSL.
- Electrical system, general utility beginning 6' from DER, 94' right of centerline, up to 5' AGL/41' MSL.
- Electrical system, general utility beginning 7' from DER, 94' left of centerline, up to 5' AGL/41' MSL.
- Fence 39' from DER, 400' right of centerline, 8' AGL/46' MSL.
- Tree 58' from DER, 495' right of centerline, 114' AGL/143' MSL.
- Tree 71' from DER, 181' left of centerline, 11' AGL/45' MSL.
- Trees beginning 306' from DER, 508' right of centerline, up to 130' AGL/146' MSL.
- Tree 510' from DER, 488' left of centerline, 109' AGL/122' MSL.
- Trees beginning 5000' from DER, 1670' right of centerline, up to 133' AGL/175' MSL.
- Tree 5317' from DER, 1828' right of centerline, 145 AGL/185' MSL.

NOTE: Chart not to scale.

### DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 20: Climb on heading 199° to 1000, then climb direct AKCOW, then climbing right turn direct UDENE, maintain 6000 or ATC assigned altitude. Expect clearance to filed altitude 10 minutes after departure.