

WAAS CH 81820 W21A	APP CRS 216°	Rwy Idg 10001 TDZE 632 Apt Elev 645
--	------------------------	--

RNAV (GPS) Z RWY 21L
DETROIT METRO WAYNE COUNTY (DTW)

RNP APCH


▼ LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS increase LNAV Cats C and D visibility to RVR 6000. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations.
***RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR



MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 direct GAAGE and hold, continue climb-in hold to 4000.

D-ATIS 133.675	DETROIT APP CON 125.15 284.0	METRO TOWER 118.4 317.725	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)	CLNC DEL 120.65	CPDLC
--------------------------	--	-------------------------------------	---	---------------------------	-------



1100	4000	GAAGE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 80).			
*LNAV only.						
1 NM 3.1 NM 3.1 NM 3.1 NM 3.1 NM 3.1 NM						
CATEGORY	A		B		C	D
LPV DA**	832/24		200 (200-½)			
LNAV/VNAV DA	1062/40		430 (500-¾)			
LNAV MDA	1040/24	408 (400-½)	1040/40		408 (400-¾)	
CIRCLING	1180-1	535 (600-1)	1180-1½ 535 (600-1½)		1240-2 595 (600-2)	

