

SUMTER, SOUTH CAROLINA

ILS or LOC Y RWY 22R

LOC I-JWU 108.7	APCH CRS 223°	Rwy Ldg 10,014	22R 8014
		TDZE 240	235
		Arprt Elev 241	241

AL-409 [USAF]

SHAW AFB (KSSC)

RADAR or DME Required.		ALSIF-1 	MISSED APPROACH: Climbing to 2000, intercept SSC TACAN R-223 to PINIE and hold.	
<p>▼* When ALS inop, increase RVR to 40 and vis to 3/4 mile. ** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1 1/4 miles.</p>				

ATIS ★ 132.125 270.1	SHAW APP CON 125.4 318.1	SHAW TOWER ★ 126.65 254.25	GND CON 126.1 275.8	CLNC DEL 126.1 275.8
--------------------------------	------------------------------------	--------------------------------------	-------------------------------	--------------------------------

Sidestep Rwy 22L: Terrain 239' MSL, 200' prior to threshold, 200' right of course.



CAUTION: Localizer only, When Rwy 4L, 22L VGSi inop, circling to Rwy 4L, 22L NA at night.

USAF Only: When Rwy 22L VGSi inop, sidestep or circling to Rwy 22L at night requires approval from MAJCOM director of Ops or equivalent.

▲
1573


LOCALIZER 108.7
I-JWU

SHAW
Chan 38 SSC



1340 ▲

EMERG SAFE ALT 100 NM 3800



ELEV 241	TDZE 22R 240
	TDZE 22L 235

HIRL all Rwy

FAF to MAP 3.7 NM					
Knots	60	90	120	150	180
Min:Sec	3:42	2:28	1:51	1:29	1:14

CATEGORY	A	B	C	D	E
S-ILS 22R*	440/24		200	(200-1/2)	
S-LOC 22R**	660/24	420 (500-1/2)	660/40	420 (500-3/4)	
SIDESTEP ** 22L	660-1	425 (500-1)	660-1 1/4	425 (500-1 1/4)	
CIRCLING	820-1 579 (600-1)	880-1 639 (700-1)	1000-2 1/4 759 (800-2 1/4)	1000-2 1/2 759 (800-2 1/2)	1000-2 3/4 759 (800-2 3/4)

SUMTER, SOUTH CAROLINA
Amdt 1 10OCT19

33° 58' N-80° 28' W

SHAW AFB (KSSC)

ILS or LOC Y RWY 22R

SE-2, 18 MAY 2023 to 15 JUN 2023

SE-2, 18 MAY 2023 to 15 JUN 2023